

# AW085C / AW095A

## 1/2" Composite Air Impact Wrench



**AW085C**



**AW095A**

### Features

- Mechanism : Twin Hammer
- Light weight with composite material
- Highest durable grade steel anvil
- Handle exhaust
- Powerful torque and excellent continuity in the same tool's field
- Forward 3 positions; Reverse : 1 position
- Hose fitting can swirl

### Applications



Automotive



Motorcycle



Industry  
Assembling Line



Agriculture  
Machine

### Features

- Mechanism : Twin Hammer
- Composite and magnesium material
- Highest durable Japanese steel anvil
- Handle exhaust
- Forward : 3 positions; Reverse : 1 position
- Nut-Busting Torque **1,200 ft-lb/ 1,620 N.m.**
- The cylinder is using material of FCD45 and has special heat treat, it has high wear resistance
- Blade with spring mounted, make sure the blades can be opened when working
- Simple structure, easy to service and repair

### Tool Specifications • AW085C : 10 Pcs/24.0 Kg/25.0 Kg/1.71' • AW095A : 10 Pcs/19.0 Kg/20.0 Kg/1.71'

Model No.	Square Drive	Bolt Capacity	Avg/Air Con.	Air Inlet	Air Pressures	Hose Size I.D.	Torque 5 Sec.	Max Torque 10 Sec.	Free Speed	Vibration	Sound Pressure Level	Overall Length	Net Weight
<b>AW085C</b>	1/2"	7/8"	5.3 CFM	1/4"	6.2 Bar	3/8"	650 FT-LB	840 FT-LB	9500 RPM	4.6 m/s <sup>2</sup>	101.9 DbA	200 mm	2.2 kg
		M24	150 L/Min		90 psi		881 N.m.	1139 N.m.				7-7/8"	4.8 LB
<b>AW095A</b>	1/2"	1"	5.5 CFM	1/4"	6.2 Bar	3/8"	800 FT-LB	950 FT-LB	8500 RPM	8.1 m/s <sup>2</sup>	91.5 DbA	179 mm	1.7 kg
		M25	158 L/Min		90 psi		1080 N.m.	1283 N.m.				6-7/8"	3.75 LB

### APACH INDUSTRIAL CO., LTD.

176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41208  
 Tel +886 4 2271 2835 Fax +886 4 2271 4840  
 www.apach-tools.com info@apach.com.tw

